



A-LineAcoustics.com

Emily

Four Piece Sub-Compact Front-Fill Modular Array



Designed to complement EMMA SOLUTIONS I, for small to medium-sized venues, sub-compact **Emily** is a front-fill array system suitable for Corporate Audio-Video applications requiring high intelligibility. The Hybrid-active bi-amped system consists of four trapezoidal enclosures (one powered EMS6A and three unpowered EMS6X extensions w/individ. Vol. controls) which can be arrayed to fill-in FOH

speakers. Also maybe used for stage monitoring or other close field applications. Powered with high quality Bang &Olufsen ICEpower, each compact 2-way enclosure comes with 1 x 6.5" Neodymium Ferro Fluid-cooled and 1x 6.5" ribbon HF driver for exceptional audio reproduction and DSP with two factory-installed programs S6A powered module and S6X ext. w/vol. control



S6A powered module and S6X ext. w/vol. control

SPECIFICATIONS	EM S6A	EM S6X
Configuration	2-Way 5 degree Trap Encl.	2-Way 5 degree Trap Encl.
Power (watts-program) HF/LF	200 / 200	200 / 200
Impedance - HF/LF	16 / 16	16 / 16
Sens. (dB@1W/1m)	94	94
Freq. Resp. (Hz) - DSP Selectable	90-18k / 125-18k	90-18k / 125-18k
x-over Frequency	2 kHz	2 kHz
HF Type	1 x 6.5" Ribbon	1 x 6.5" Ribbon
Horizontal Dispersion	120 degrees	120 degrees
LF Driver (Ferro Fluid-Cooled)	1 x 6.5"	1 x 6.5"
Amp - B&O ICEPower Dual Volt. w/DSP	200 RMS HF / 1000W LF	N/A – Vol. Control
Connectors	M&F XLR, I/O Powercon	2 x NL4 + Vol. Control
HxWxD (inches)	7.13 " x 13.13" x 11.5"	7.13 " x 13.13" x 11.5"
Weight (lbs./kg.)	14 / 6.4	12.2 / 5.5

Included Accessories: 3 ea. 10' NL4 – NLR4 cables & 1 ea. 25' AC Main

MADE IN USA

Specifications subject to change without notice

Manufacturing and Distribution

510 East Washington Street, Corry, PA 16407 Tel. 814-663-0600 Fax. 814-664-7429

Marketing and Sales

4608 Cliff Drive Erie, PA 16511 Tel. 814 464-0631 mgorczycki@a-lineacoustics.com